

LT-731 MICROPROCESSOR DISINTEGRATION TEST APPARATUS

2 BASKET



PRODUCT FEATURES

- ✓ Complies with USP, IP specifications
- ✓ Extremely useful for pharmaceutical labs
- ✓ Highly Accurate and Easy to Operate
- ✓ Baskets 'UP' & 'DOWN' movement as per IP/USP Specifications
- ✓ Graphical LCD display
- ✓ 15 Soft Touch Membrane Type Keys
- ✓ 20 Setups Storage Facility
- ✓ 400 Samples Storage Facility
- ✓ USB interface available.
- ✓ Audio Visual Indicators for System Status

ACCESSORIES

- ✓ External Temperature Sensor
- ✓ Mains Lead
- ✓ Instruction Manual
- ✓ Dust Cover



TECHNICAL SPECIFICATIONS

Display	Graphical LCD display
Keyboard	15 soft touch membrane keys
LED's	4 LED's available for different status indications. 3 LED's for Test status like Run, Alarm, End and one LED for heater on/off status.
Setup Data	Facility for 20 different test setups available
Printer	Provision for the attachment of dot-matrix printer with centronics parallel port interface
Speed	55 mm. 30 ± 1 strokes per minute
Resolution	1 Sec - 99 Minutes
Temp. Range	20°C - 50°C
Temp. Accuracy	± 0.2 °C
Temp. Control	Microprocessor based using PT100/Semiconductor Sensor
Reaction Beaker	1000 ml
Heater	0.4 KW (Approx.)
PC Connectivity	USB interface available
Power	230 V ± 10% AC, 50 Hz
Dimensions	365 x 350 x 495 mm (L x B x H) (Approx.)
Weight	9 Kg (Approx.)



LABTRONICS®
Always a step ahead in technology...

All Designs And Specifications are subject to change without prior notice.